

DATA SHEET

RESIN CORED SOLDER S. A. B. S. GRADE 40T2

DESCRIPTION:

“NASCO” 40T RESIN CORED SOLDER IS A TRIPLE CORED HIGH GRADE SOLDER ALLOY MADE ONLY FROM VIRGIN MATERIAL. THE ROSIN FLUX IS A WATER WHITE GUM ROSIN MILDLY ACTIVATED WITH A VERY EFFECTIVE ACTIVATING AGENT. THE DRY FLUX RESIDUE AFTER SOLDERING HAS VERY GOOD ELECTRICAL INSULATING PROPERTIES. THIS FLUX IS NON CORROSIVE. “NASCO” QUALITY SOLDERS COMPLY WITH MOST NATIONAL AND INTERNATIONAL STANDARDS.

AVAILABILITY:

STANDARD FLUX AND LOW RESIDUE EX STOCK.

COMPOSITION:

Sn	39 - 41%
Cu	0.10% MAX.
Sb	0.10% MAX.
Bi	0.10% MAX.
As	0.05% MAX.
Fe	0.02% MAX.
Pb	BALANCE

IDENTIFICATION.

RESIN CORED SOLDER REELED ON RED REELS.

PACKING.

500 gm. REELS - 20 PER CARTON