

NATIONAL SOLDER

CO

PO BOX 1258
GERMISTON
GAUTENG 1400

Phone: (2711)8739000
FAX: 011 8254528
e-mail:solders@nationalsolder.com

Material Safety Data Sheet

HT3 Resin Core SOLDERS (Tin/Antimony Alloys)

Section I:

NATIONAL SOLDER CO Telephone 011-873-9000
13 ARKIN STR, INDUSTRIES EAST
GERMISTON, SOUTH AFRICA

Section II:

Hazardous Ingredients/Identity information

Hazardous Component CAS # OSHA TWA ACGIH TWA Other limits Percentage
+ Antimony 7440-36-0 0.5mg/M3 0.5mg/M3 NE as specified

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.

An ingredient marked with an asterisk(*) is also listed in 29CFR 1910.1200 (D) #4 as a known or suspected cancer hazard.

+ Denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40 CFR Part 372 (Section 313) (SARA Title III).

Section III:

Physical/Chemical Characteristics

COMPOSITION: Tin (84.5- 85.5)
Antimony (4.5-5.5)
Gum Rosin (2.0-2.5)

Melting Point: 234 C

Vapor Density: NA Evaporation Rate

Solubility in water: insoluble (butyl acetate=1): NE

Liquidus: 232 C

Solidus: 240 C

Appearance and odor: Grey solid, odorless

Section IV:

Fire and Explosion Hazard Data

Flash Point: NA Flammable limits lel: NAP uel: NAP

Extinguishing media: Dry chemical, do not use water

Special fire fighting procedures: Use self contained breathing apparatus.

Unusual Fire and Explosion Hazards: High concentrations of dust may present an explosion hazard.

May release metal and metal oxide fumes.

Section V:

Reactivity Data

Stability : STABLE Conditions to avoid : none

Incompatibility (materials to avoid):Oxidizers, strong acids, turpentine, halogens

Hazardous Decomposition or By products: Metal fumes, metal oxides.

Hazardous Polymerization: WILL NOT OCCUR Conditions to avoid: none

Section VI:

Health Hazard Data

Routes of entry: Inhalation? yes Skin? no Ingestion? yes

Health Hazards (acute and chronic): Contact with material, dust and fumes may cause skin, eye and respiratory tract irritation. Excessive inhalation of dust or fumes may result in "metal fume fever", with the onset of symptoms taking several hours after exposure to manifest.

Ingestion may cause digestive tract irritation. Ingestion of very large amounts of material may be toxic. Excessive and repeated inhalation may result in benign pneumoconiosis. Chronic exposure via inhalation and ingestion may result in liver, red blood cell, kidney, reproductive and respiratory system effects. Excessive and repeated skin exposure may result in systemic effects including pigmentation changes. Studies show that potential health risks vary by individual. Always minimize exposure. May be mutagenic in lab animals.

Carcinogenicity: not determined NTP? no; IARC Monographs? no

Signs and symptoms of exposure: Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, flu like symptoms, greyish skin palor.

Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash, dryness. Eye-redness, burning, tearing, blurred vision.

Medical Conditions Aggravated by exposure: Respiratory tract, skin, blood conditions.

Emergency first aid procedures:

Skin: Flush with water immediately - Treat for burns, seek medical attention if required

Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: Drink large amounts of water, induce vomiting if practical-seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Support respiration if required.

Seek medical attention if required.

Section VII:

Precautions for Safe Handling and Use

Steps to be taken if material is released or spilled: Collect and use, if contaminated or in small particles, vacuum or collect material. Never use methods which generate dust.

Waste Disposal Method: Never dispose of in trash. Hold for recycling or dispose of in accordance with all local, state regulations.

Other Precautions: Avoid skin & eye contact, inhalation & ingestion of fumes and material.

Wash contaminated clothing before reuse. Keep away from children. Do not reuse container.

Section VIII: Control Measures

Respiratory Protection (type): Dust mask for particulates. Metal fume type respirator for fumes.

Ventilation Local Exhaust preferred Special: NE

Mechanical: OK Other: NE

Protective Gloves: Heat resistant during soldering

Eye Protection: Goggles or face shield during soldering

Other Protective Clothing or Equipment: as required to avoid contact.

Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

Section IX: Additional Information: Lead Free and ornaments made from this material is food safe.

DOT Classification: non-hazardous

Other: NE

Delivery Information

International delivery regulation: LATA- Dangerous Goods Regulation, Not Restricted.

UN code: Not Regulated

Domestic Delivery Regulation: None known

Special delivery method and precaution: None known

Law and Regulation

Conform to regulation; 1. SABS regulation
materials. 2. Identification rules for hazardous and harmful
requirement. 3. Standards for waste disposal treatment and facility
4. Road traffic safety rules.

Additional Information

Reference: MSDS database, CCINFO CD 98-2, NIOSH/OSHA, Occupational Health Guidelines for Chemical Hazards, 1981. Product is used as pewter and is foodsafe.

Prepared by: Kirit Daya

=

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to National Solder Co at the time of issue. No warranty, guarantee, or representation is made by NATIONAL SOLDER CO nor does NATIONAL SOLDER CO assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances.

NE = not established NA = not available NAP = not applicable